



ST0488




ST0488 VERSION LUGE



ST0491



NW0591



NW0588F



NW0590/G



NW0620

		ST0488	ST0488 VERSION LUGE	ST0491	NW0591	NW0588F	NW0590/G	NW0620F
Nombre de phases		Monophasé	Monophasé	Monophasé	Monophasé	Monophasé	Monophasé	Monophasé
Tension primaire	V	230	230	230	230	230	230	230
Fréquence primaire	Hz	50	50	50	50	50	50	50
Intensité primaires	A	6.1	6.1	8.8	8.8	6.1	8.8	15
Tension secondaire	V	42 3 ~	42 3 ~	42 3 ~	42 3 ~	42 3 ~	42 3 ~	42
Fréquence secondaire	Hz	200	200	200	200	200	200	200
Intensité secondaire	A	14	14	23	23	14	23	35
Puissance	kVA	1	1	1.6	1.6	1	1.6	2.5
Nombre de prise		1	1	2	2	1	2	3
Poids	kg	16	17.5	23.5	25	22	28	37
Dimensions chassis L x l x H	cm	29 x 20 x 35	48 x 20 x 38	48 x 20 x 38	48 x 20 x 31	56 x 26 x 37	56 x 26 x 37	56 x 26 x 37
Montage d'aiguilles en simultané		1 Ø 38 mm ou 1 Ø 50 mm	1 Ø 38 mm ou 1 Ø 50 mm	2 Ø 38 mm ou 2 Ø 50 mm ou 1 Ø 60 mm ou 1 Ø 70 mm	2 Ø 38 mm ou 2 Ø 50 mm ou 1 Ø 60 mm ou 1 Ø 70 mm	1 Ø 38 mm ou 1 Ø 50 mm	2 Ø 38 mm ou 2 Ø 50 mm ou 1 Ø 60 mm ou 1 Ø 70 mm	3 Ø 38 mm ou 3 Ø 50 mm ou 2 Ø 60 mm ou 1 Ø 70 mm
Référence		0502301000 ☒	0502301001 ☒	0502301002 ☒	0502301005 ☒	0502301006 ☒	0502301007 ☒	0502301008 ☒